


375 IN Double


P2.5
P2.9
P3.9

MODULE PARAMETERS			
Pixel pitch	2.5 mm	2.98 mm	3.91 mm
Module size	250 x 250 mm		
LED type	SMD1515		SMD 2121
Module resolution	100 x 100	84 x 84	64 x 64
CABINET SPECIFICATIONS			
Cabinet size	500 x 250 x 53 / 1,000 x 250 x 53		
Cabinet Materials	Aluminium		
TECHNICAL SPECIFICATIONS			
Weight	31 Kg/sqm		
Brightness	800 nits	800-1,000 nits	1,000-1,200 nits
Contrast ratio	5,000:1		
Viewing Angle	160°V - 160°H		
Gray level	16		
Refresh Rate	3,840 Mhz		
Power Input	110 - 220 V		
Power consumption Maximun	750 W	800 W	730 W
Power consumption Average	180 W	195 W	150 W
Life--hours	> 100,000		
IP grade	IP63 Front / IP63 Back		
Operating Temperature	from -20 ~60		
Storage Humidity	10% - 90% RH		
Maintenance access	Front		
ECOACTIVE FEATURES			
Nox & Sox Abatement	50.03%		
Certification of pollution abetment	ISO 22197 from Fraunhofer institut		
Antidust	Yes		
Self-cleaning	Yes		
Anti-bacterial	Yes		