


375 IN Shield



P1.25 P1.5 P1.8 P2.5

MODULE PARAMETERS				
Pixel pitch	1.25 mm	1.56 mm	1.875 mm	2.5 mm
Module size	300 x168.75 mm			
LED type	SMD1010	SMD1212	SMD1515	
Module resolution	240 x 135	192 x 108	160 x 90	120 x 68
CABINET SPECIFICATIONS				
Cabinet size	600 x 337,5x 63 mm			480 x 480 x 63 mm
Cabinet Materials	Aluminium			
TECHNICAL SPECIFICATIONS				
Weight	29 Kg/sqm			
Brightness	800-1,200 nits			
Contrast Ratio	5,000:1			
Viewing Angle	160°V - 160°H			
Gray level	16			
Refresh Rate	3,840 Mhz			
Power Input	110 - 220 V			
Power consumption Maximun	600			
Power consumption Average	180			
Life--hours	> 100,000			
IP grade	IP65 Front / IP43 Back			
Operating Temperature	from -20 ~60			
Storage Humidity	10% - 90% RH			
Maintenance access	Front			
ECOACTIVE FEATURES				
Nox & Sox Abatement	50.03%			
Certification of pollution abetment	ISO 22197 from Fraunhofer institut			
Antidust	Yes			
Self-cleaning	Yes			
Anti-bacterial	Yes			

