

## 375 IN Ultraslim



**P2.5**

**P2.9**

**P3.9**

MODULE PARAMETERS			
Pixel pitch	2.5 mm	2.98 mm	3.91 mm
Module size	250 x 250 mm		
LED type	SMD1515		SMD 2121
Module resolution	100 x100	84 x 84	64 x 64
CABINET SPECIFICATIONS			
Cabinet size	1,000 x 250 mm   750 x 250 mm		
Cabinet Materials	Aluminium		
TECHNICAL SPECIFICATIONS			
Weight	23.2 Kg/sqm		
Brightness	800 nits	800 -1,000 nits	1,000-1,200 nits
Viewing Angle	160°V - 160°H		
Gray level	14 / 16 Optical		
Refresh Rate	3.840 Mhz		
Power Input	AC90-264V		
Power consumption Maximun	800 W/m2		
Power consumption Average	100 - 200 W/m2		
Life--hours	> 100,000		
IP grade	IP43		
Operating Temperature	from -20°C~60°C		
Storage Humidity	10% - 90% RH		
Maintenance access	Front		
ECOACTIVE FEATURES			
Nox & Sox Abatement	50.03%		
Certification of pollution abetment	ISO 22197 from Fraunhofer institut		
Antidust	Yes		
Self-cleaning	Yes		
Anti-bacterial	Yes		

