

375 OUT +



P2.9 P3.9 P4.8 P5.7 P6.6 P8 P10

| MODULE PARAMETERS | | | | | | | |
|-------------------------------------|------------------------------------|-----------------------|-----------------------|------------|---------|------------|---------|
| Pixel pitch | 2.9 | 3.9 | 4.8 | 5.7 | 6.6 | 8 | 10 |
| Module size | 500x250 | | | 160x160 | | | |
| LED type | SMD1921 | SMD1921 | SMD1921 | SMD2727 | SMD2727 | SMD3535 | SMD3535 |
| Module resolution | 168x84 | 128x64 | 104x52 | 28x28 | 24x24 | 20x20 | 16x16 |
| CABINET SPECIFICATIONS | | | | | | | |
| Cabinet size | 500x500 | 500x500/ 500x1,000 | 500x500/ 500x1,000 | 960x960 | | | |
| Cabinet Materials | Aluminium | | | | | | |
| TECHNICAL SPECIFICATIONS | | | | | | | |
| Weight | 34 Kg/sqm | | | | | | |
| Brightness | 4,000 nits | 5,000 nits | | 6,000 nits | | 7,000 nits | |
| Viewing Angle | 160°V - 160°H | | | | | | |
| Gray level | 16 | | | | | | |
| Refresh Rate | 3,840 Mhz | | | | | | |
| Power Input | 110 - 220 V | | | | | | |
| Power consumption Maximun | 650 | | | 520 | | | |
| Power consumption Average | 170 | | | 130 | | | |
| Life--hours | > 100,000 | | | | | | |
| IP grade | IP65 | | | | | | |
| Operating Temperature | from -20 ~60 | | | | | | |
| Storage Humidity | 10% - 90% RH | | | | | | |
| Maintenance access | Front / Rear | | | | | | |
| ECOACTIVE FEATURES | | | | | | | |
| Nox & Sox Abatement | 50.03% | | | | | | |
| Certification of pollution abetment | ISO 22197 from Fraunhofer institut | | | | | | |
| Antidust | Yes | | | | | | |
| Self-cleaning | Yes | | | | | | |
| Anti-bacterial | Yes | | | | | | |