

## 375 OUT Flexible



	<b>P3.81</b>	<b>P6.67</b>
<b>MODULE PARAMETERS</b>		
<b>Pixel pitch</b>	P3.81	P6,67
<b>Module size</b>	304.8 x 304.8 mm	320 x 320 mm
<b>LED type</b>	SMD1921	SMD2727
<b>Module resolution</b>	W80 x H80	W48 x H48
<b>Smallest Circle Diameter</b>	582 mm	
<b>TECHNICAL SPECIFICATIONS</b>		
<b>Brightness</b>	5,000 nits	6,000 nits
<b>Viewing Angle</b>	160°V - 160°H	
<b>Gray level</b>	16 bits	
<b>Refresh Rate</b>	3,840 Mhz	
<b>Power Input</b>	110 / 220 V	
<b>Power consumption Maximun</b>	532	843
<b>Power consumption Average</b>	120	190
<b>Life--hours</b>	> 100,000	
<b>IP grade</b>	IP68 Front / IP68 Back	
<b>Operating Temperature</b>	from -20 ~60	
<b>Storage Humidity</b>	10 ~90 RH	
<b>Maintance access</b>	Front	
<b>ECOACTIVE FEATURES</b>		
<b>Nox &amp; Sox Abatement</b>	50.03%	
<b>Certification of pollution abetment</b>	ISO 22197 from Fraunhofer institut	
<b>Antidust</b>	Yes	
<b>Self-cleaning</b>	Yes	
<b>Anti-bacterial</b>	Yes	