


375 IN Multi-size



1.56

P. 1.95

P2.6

P3.9

Module Parameters				
Pixel pitch	1.56mm	1.95mm	2.6mm	3.9mm
Module size	250 x 250 mm			
LED type	Flip Chip COB			
Module resolution	160 x 160	128 x 128	96 x 96	64 x 64
Cabinet Specifications				
Cabinet size	500 x 250 250 x 500 500 x 500 500 x 1000mm			
Cabinet Materials	Die-casting aluminum			
Technical Specifications				
Cabinet Weight	3.2Kg 5.6Kg 11kg			
Brightness	600 – 800 nits	800 – 1000 nits	1000 – 1200 nits 1000 – 4500 nits	
Contrast Ratio	6,000:1			
Viewing Angle	179°V – 179°H			
Gray level	14 – 16 bits			
Refresh Rate	3,840 Mhz			
Power Input	AC200~AC240			
Maximum Power consumption	224 W/sqm	340 W/sqm	480 W/sqm	500 W/sqm
Power consumption Average	77 W/sqm	120 W/sqm	160 W/sqm	170 W/sqm
Life--hours	> 100,000			
IP grade	IP20 Front / IP30 Rear			
Operating Temperature	from -20°C~60°C			
Storage Humidity	10% – 90% RH			
Maintenance access	Front or Rear			
EcoActive Features				
Nox & Sox Abatement	50.03%			
Certification of pollution abetment	ISO 22197 from Fraunhofer institut			
Antidust	Yes			
Self-cleaning	Yes			
Anti-bacterial	Yes			