





DUCATIONAL



New Pro Frame Professional Frame Screen

SCREENLINE



16:9 16:10 4:3 New Pro Frame

350

400

Professional Frame Screen. It stands out for its easy and quick installation. Designed and built using 4Rent's aluminium profile, it features a smarter shape/silhouette thanks to the the 45° corner. It ensures Made in Italy products' high quality and finds its place in the rental market as well as the installers and professionals markets.

150

200

250

300

SCREEN CHARACTERISTICS

550

450

650

- smart and robust aluminium profile
- wide range of fabrics
- T-stands for floor application on request
- RGB LED back lighting stripe compatible with all home automation control systems (on request)
- customized sizes

SURFACE OPTIONS

- Diamond
- Microperforated
- Perforated
- Ambra rear projection
- Dual face



Do you know Arrow Border?

It is the new tongue and groove system which makes the screen installation quick and easy. Thanks to its new border, the fabric is pressed into the groove and matches the whole perimeter of the frame stretching homogeneously.

Grooves: On the back of the screen, the installer can choose between 2 grooves in which to fix the fabric. This choice allows to obtain the best result as to tensioning and flatness, so correcting any possible over-stretching of the PVC.

 $\star The innermost groove must not be used. The black arrow border of the fabric would be visible during projection.$







Wall brackets

Made of aluminium, they allow wall mounting for permanent or semi-permanent installations.

Eye bolts

Made of stainless steel, they are suitable for steel chains or other supports for installations on truss structures or others

T-stands

Designed for positioning the screen on the floor, they are made of matt, anti-reflex, high-resistance aluminium with black finish (3 cm section). The extension is obtained by rotating the upper profile which features some holes to anchor the screen at different levels. The floor anchoring is possible thanks to the horizontal segments which can be lowered separately and blocked by special reinforcement 45° joints.

The product comes with PVC locking screws with black butterfly knobs. Once it is closed, it is light and compact for easy transportation.



screenline.it